

Aluminum oxide abrasive grain is bonded to a non-woven nylon mesh with synthetic resins to make products that are more resistant to loading and less aggressive than coated abrasives for cleaning, finishing, blending, and deburring on a variety of different materials.

Hand Pads - Aluminum Oxide

Resistant to loading and less aggressive than coated abrasives for cleaning, finishing, blending, and deburring on a variety of different materials. Washable.



60000

Description	Size Length x Width	Standard Pack Per Case	Item Number
All Purpose Pad (Maroon)	6 x 9	1 Case (60 pcs.)	60000
Ultra Fine Pad (Grey)	6 x 9	1 Case (60 pcs.)	60246
Standard Duty Pad (Green)	6 x 9	1 Case (60 pcs.)	61768
Heavy-Duty Pad (Green)	6 x 9	1 Case (60 pcs.)	61770
Heavy-Duty, Long-Life Pad (Tan)	6 x 9	1 Case (40 pcs.)	65470

For special pricing on full pallet orders, contact Customer Service.



66970

A - Aluminum Oxide
VF - Very Fine
M - Medium
F - Fine

Stem-Mounted Discs

For light blending, finishing, and cleaning applications on contoured or irregular surfaces of large parts.



Diam. x Width x Stem	Abrasive Type/Grade	Max. RPM	Standard Pack	Item Number
2 x 1/2 x 1/4	A-M	12,000	10	66970
2 x 1/2 x 1/4	A-VF			66971
2 x 1 x 1/4	A-M			66972
2 x 1 x 1/4	A-VF			66973
3 x 1/2 x 1/4	A-M	8,000	10	66974
3 x 1/2 x 1/4	A-VF			66975
3 x 1 x 1/4	A-M			66976
3 x 1 x 1/4	A-VF			66977



68241

Stem-Mounted Interleaf Flap Wheels

Flaps of coated abrasive cloth are alternated with Anderlex non-woven material resulting in more aggressive action for surface cleaning or preparation, blending, and finishing applications on all types of metals.



Diam. x Width x Stem	Grit Size	Max. RPM	Standard Pack	Item Number
2 x 1 x 1/4	120	15,000	10	68240
	180			68241
3 x 1/2 x 1/4	120	8,600	5	68243
	180			68244
3 x 1 x 1/4	120	8,600	5	68246
	180			68247
3 x 2 x 1/4	120	8,600	5	68249
	180			68250