



03789

## Andermax™ High-Density Crimped Wire Wheels - DMXX Series

Large diameter wheels used for rubber buffing, edge blending, gear deburring and flash removal on specialized equipment.

Diam.	Wire Size	Arbor Hole	Trim Length	Face Width	Width at Faceplate	Max. RPM	Catalog Number	Standard Pack	Item Number Steel
12	.006 .0118 .014	2•	1-5/8	1-1/8	3/4	3,000	DMXX12-7	1	04329 04349 04359
12	.006 .0118	2•	3/4	3/4	13/16	3,000	DMXX12-9	1	03789 03809
14	.0118	1-1/4°	1-3/4	7/8	13/16	2,400	DMXX14-9	1	03968
15	.0118	2•	2-1/4	1	13/16	2,400	DMXX15-9	1	03889

• 1/2 x 1/4 Double Keyway ° 1/4 x 1/8 Double Keyway

Refer to page 28 for Adapters and Drive Arbors.



27073


## Tampico Wheel - SS Series

For delicate brushing and finishing.



Diam.	Arbor Hole	Trim Length	Face Width	Width at Faceplate	Max. RPM	Catalog Number	Standard Pack	Item Number Tampico
3	1/2-3/8	1	1/2	3/8	20,000	SS30TN	10	27073

Refer to page 28 for Adapters.



26769

## Tampico Wheels - QTAM & TAM Series

For delicate brushing and finishing.



Diam.	Arbor Hole	Trim Length	Face Width	Width at Faceplate	Max. RPM	Catalog Number	Standard Pack	Item Number Tampico
6	2	1-1/2	17/32	17/32	6,000	QTAM6N	5	26769
8	3-1/4	1-7/8	17/32	1/2	5,000	TAM8N	5	27310
10	3-1/4	2-27/32	17/32	1/2	4,500	TAM10N	2	27330
12	4-1/4	3-3/8	17/32	17/32	4,000	TAM12N	2	27350

Refer to page 28 for Adapters and Drive Arbors.



72016

## Nylon Wheels - SS Series

For delicate, scratch-free finishing.



Diam.	Fill Diam.	Arbor Hole	Trim Length	Face Width	Max. RPM	Catalog Number	Standard Pack	Item Number Nylon
1-1/2	.010	3/8	7/16	1/4	20,000	SS14Y	10	27078
2	.010	1/2	1/2	3/8	20,000	SS20Y	10	72016
3	.016	5/8	15/16	1/2	20,000	SS30Y	10	70423